

# PVXC5 Sensor Cable Extension

DATASHEET

for Stingray Level-Velocity Loggers and MantaRay Portable Area-Velocity Flow Meters



## Specifications

**Cable Length:** 15 m (50 ft)

**Submersion Rating:** IP68

**Operating Temp:** -15 °C to 65 °C  
(5 °F to 150 °F)

**Exposed Materials:** Glass-filled  
Polyamide, PVC

## Cable & connectors rated IP68 for continuous submersion

Extend sensor cable an additional 15 m (50 ft) with one PVXC5 Sensor Cable Extension connected between the meter enclosure and the sensor. The extension includes watertight, submersible connector plugs.

NOTE: Use only one PVXC5 Sensor Cable Extension for a total cable length of 23 m (75 ft).



INFO@PULSARMEASUREMENT.COM

Pulsar Measurement is a trading name of Pulsar Process Measurement, Ltd.

Copyright © 2021 Pulsar Measurement  
Registered Address: 1 Chamberlain Square CS, Birmingham B3 3AX  
Registered No.: 3345604 England & Wales

## Delivering the Measure of Possibility

**United States**  
+1 888-473-9546

**Asia**  
+60 102 591 332

**Canada**  
+1 855-300-9151

**Oceania**  
+61 428 692 274

**United Kingdom**  
+44 (0) 1684 891371

**pulsarmeasurement.com**

Rev 1.0